



GS-671 PRIMER

✔ LVT/LVP installations ✔ SELF LEVELING underlayment ✔ TILE BONDING primer

PRODUCT DESCRIPTION

GS-671 Primer is a premium emulsion polymer that cures as a strong flexible **penetrating bonding primer** for all glue-down luxury vinyl tile and plank products, vinyl-backed carpet tile, and self leveling underlayments. Also use as a bonding primer before thin-setting tile, porcelain tile and natural stone to difficult surfaces (see approved surfaces).

APPROVED SUBSTRATES

- Gypcrete
- Lightweight concrete
- Porous Concrete
- Self-leveling underlayment
- OSB
- Plywood

SURFACE PREPARATION

All substrates must be structurally sound, clean and dry. Surfaces must not contain dirt, oil, grease or any contaminant that would prevent bonding. All existing flooring finishes must well bonded to substrate. All surfaces must not be subject to moisture levels exceeding 6 lbs./1,000 (MVER). Surfaces cannot be subject to hydrostatic pressure or contain efflorescence.

COVERAGE

400 sq. ft. per gallon

PACKAGING

5 gallon pail

APPLICATION

GS-671 Primer is a ready to use formula so there is no mixing required before use. Substrate and ambient temperature must be between 32°F to 100°F. Pour primer on floor and apply with a 3/8" nap roller or pump sprayer. Do not allow primer to puddle. GS-671 Primer only requires 1 coat but 2 coats can be applied after the first coat is dry.

DRY TIME

30 minutes *(depending on ambient conditions)*

CLEAN UP

Clean tools or non-desired primed surface with water immediately after use.

STORAGE & PROTECTION

Primed surface must be protected from direct sunlight & contamination.

CAUTION: DO NOT FREEZE.

Typical shelf life of 12 months in unopened container.

PRODUCT WARRANTY

Surface primer warrant that its product shall be free from defects in the material under proper usage for a period of one year from original purchase date. Material safety data sheet available upon request. Keep out of the reach of children.

TILE ADHESION

Install tile or stone with an (118.4) latex-modified thinset mortar.

LIMITATIONS

Do not apply over dusty or structurally unstable substrates. Do not use as a wear surface.

STEP 1 - use GS-671 PRIMER
STEP 2 - use GS-672 ADHESIVE