



GS-672 ADHESIVE

IDEAL FOR • VINYL-BACKED LVT • LVP • CARPET TILE

PRODUCT DESCRIPTION

GS-672 Adhesive is a multi-purpose flooring adhesive designed for vinyl-backed LVT, LVP and carpet tile. It is packaged in ready-to-use 4-gallon buckets. GS-672 Adhesive has a mastic consistency and is designed to be applied with a trowel or roller. When applied properly to a non-porous substrate, a 4 gallon pail will cover approximately 1000–1200 sq. ft. of flooring. GS-672 has an extended working time of up to 12 hours depending on temperature and relative humidity. Allow adhesive 24 hours to cure before walking or placing furniture on newly installed flooring. Use in interior spaces only and consult Safety Data Sheet (SDS) prior to use.

- Typical application methods include troweling or roller coating.
- GS-672 Adhesive can be applied in high relative humidity applications (up to 98% RH) and is compatible with alkaline concrete.
- GS-672 Adhesive is packaged in 4-gallon pails with 48 pails stretch-wrapped per pallet.

CAUTION: DO NOT FREEZE.

Typical shelf life of 12 months in unopened container.



TYPICAL PHYSICAL PROPERTIES

Certificate of analysis will be included with each shipment. Laboratory retains from each lot are kept on-site at GreenSeel™ Products Company for 1 year after production.

Adhesive Base:	Acrylic Polymer Emulsion (Pressure Sensitive)
Pounds/Gallon:	8.4 – 8.8 #/gal.
Solids (non-volatile):	50 – 56%
pH:	7–9
Viscosity:	Mastic paste
Color:	Off-white, mildly tan

STEP 1 - use GS-671 PRIMER
STEP 2 - use GS-672 ADHESIVE

WWW.GREENSEELPRODUCTS.COM

