



GS-672 ADHESIVE

IDEAL FOR LVT • LVP • VINYL-BACKED PLANK, TILE, & CARPET

PRODUCT DESCRIPTION

GS-672 is a multi-purpose flooring adhesive designed for vinyl-backed plank, tile, and carpet. It is packaged in ready-to-use 4-gallon pails with labeling according to customer specifications. GS-672 has a mastic consistency and is designed to be applied with a trowel. When applied properly to a non-porous substrate, 1 pail should cover a maximum of 1000–1200 sq. ft. of flooring. GS-672 has an extended working time of up to 12 hours depending on temperature and relative humidity. Allow adhesive 24 hours to cure before walking or placing furniture on newly installed flooring. Use in interior spaces only and consult Safety Data Sheet (SDS) prior to use.

- Typical application methods include troweling or roller coating.
- GS-672 can be applied in high relative humidity applications (up to 98% RH) and is compatible with alkaline concrete.
- GS-672 is packaged in 4-gallon pails with 48 pails stretch-wrapped per pallet.

CAUTION: DO NOT FREEZE.

Typical shelf life of 12 months in unopened container.



TYPICAL PHYSICAL PROPERTIES

Certificate of analysis will be included with each shipment. Laboratory retains from each lot are kept on-site at GreenSeel™ Products Company for 1 year after production.

Adhesive Base:	Acrylic Polymer Emulsion
Pounds/Gallon:	8.4 – 8.8 #/gal.
Solids (non-volatile):	50 – 56%
pH:	7–9
Viscosity:	Mastic paste
Color:	Off-white, mildly tan

